Table of Contents

	Page
Acknowledgement	iii ·
Abstract (Thai)	iv
Abstract (English)	V
Table of Contents	vi :
List of Figures	xi
Abbreviations and Symbols	xviii
Chapter 1: Introduction	01
1.1 Background of Vietnam	01
1.1.1 The history of Vietnam	01
1.1.2 The overview of Vietnamese architecture in the	07
period of the last feudalism (1802-1945) and the	
French-domination (1858 – 1954)	
1.2 Background of the Hue City	\\9
1.2.1 History of the Hue City	9
1.2.2 The Hue historical architecture in the period of	13
the last feudalism of Vietnam and French	-
domination	. II.
1.3 Background of the Bao Vinh Village	14
1.4 Problem Statements	18
1.5 Objectives of the Thesis	20
1.6 Significances of <i>Tu Giac</i> houses	21
1.7 Hypothesis	22
1.8 Research Design & Procedure	22
1.9 Conclusions of Chapter 1	25
Chapter 2: Literature Review	26
2.1 The Citadel and the <i>Ruong</i> House in Hue City	26
2.1.1 The Citadel	26
2.1.2 Ruong House Map and its commonly application of	31
Architecture in Hue City	2.4
2.2 Tu Giac Housing Type - The harmonious mixing of Hue	34
traditional and French-influenced architecture	131
2.3 Literatures on Architectural Conservation of the Hue City	41
2.3.1 Science, Technology, Conservation, and	41
Restoration of Architectural Monuments	reit
(2003 and 2007)	1311
2.3.2 Hue Cultural Heritage – The Promotion of <i>Tu</i>	42
Giac House Conservation (2002)	e . (
2.3.3 The Guideline for Conserving Hue Traditional	43
House (2003)	
2.3.4 The source of Hue Traditional Houses as	44
references to Tu Giac Houses (2004)	

2.4 Related Charters, Laws, and Principles of Conservation	45
2.4.1 Venice Charter (1964)	46
2.4.2 ICOMOS Charter – Principles for the	48
analysis, conservation and structural	
restoration of architectural heritage (2003)	
2.4.3 Principles for the Preservation of	48
Historic Timber Structures (1999)	
2.4.4 Law on Cultural Heritage of Vietnam (2001)	49
2.4.5 Ruong house Conservation Principles,	49
Hue City – Vietnam (2003)	
2.5 Conclusions of Chapter 2	52
Chapter 3: Methodology- Descriptive Analysis to define the	
Historical Values and Outstanding Architectural	
Characteristics of Tu Giac Houses	11
3.1 The Outstanding Characteristics of the <i>Tu Giac</i> houses (A ₁ –	58
A_6	
3.1.1 The Load Bearing Walls	58
3.1.1.a Three-sided Load Bearing Walls	58
(north, south, east)	/ /
3.1.1.b The dependent bracing supports	59
from the timber beams on the	
missing load-bearing wall	
3.1.1.c The non-existence of bracing frame	60
of the inside walls	
3.1.1.d The <i>Vo</i> bricks	61
3.1.1.e The rareness of Load Bearing Walls	61
in Hue's today Architecture	
3.1.2 Two-Storey Buildings	62
3.1.2.a The rareness in Hue traditional 2-	62
storey architecture	
3.1.2.b The low interior spaces below	63
living standards and the short buildings	9-7-9
3.1.3 The high-pitch Timber Stair	64
3.1.3.a The resembling of Hue traditional	64
multi-storey buildings	Certy
3.1.3.b The high pitch and small width	65
staircase to utilize the limited ground	-
floor area	e . (
3.1.3.c The rareness high-pitched stairs in	6/
today architecture of Hue city	

3.1.4 The Timber Floor		57
	\mathcal{E}	57
	ture (<i>Ruong</i> House) areness of <i>Kien Kien</i> timber	58
	today architecture in Hue	
City	1467	.
3.1.5 The Hip Roof		59 59
	in the Hue City traditional	,,
architec	ture	
	1	70
	Liet tiles aditional roof-composition of 7	72
three tile		_
	•	74
		75
roof ridge 3.1.6 The Entrance Door		75
	s using filled-in Horizontal 7 The Slat Shutter Windows	75
		75
filled-in	horizontal wooden panels	
	presenting the historical street	
7	ouses of the old towns in Vietnam	
		77
	a filled-in horizontal wooden	,
panels d	loor	
		77
Window	vs of the hot and humid	
3.2 A typical <i>Tu Giac</i> House and Its	Architectural Elements 7	78
3.3 Deteriorations & Destructions of	f <i>Tu Giac</i> House 8	31
3.3.1 The Load Bearing		33
3.3.1.1 Crack 3.3.1.2 Moss		33 36
		37 37
	akiness of plaster and	37
	_	39
3.3.2 Two-Storey Buildin		39
	ncroachment of additional 8	39
parts 3.3.3 The high-pitch Tim	nher Stair	90
3.3.3.1 Crack		90
		91
pest at	ttacks	

3.3.3.3 The damage of endpoints	92
3.3.3.4 The movement out of its original	93
position	
3.3.3.5 The encroachment on the original	93
narrow access	
3.3.4 The Timber Floor on the 2 nd level	94
3.3.4.1 Cracks on floor beams and planks	94
3.3.4.2 The change of the original timber	95
planks	
3.3.4.3 The aging of wood and the fungal	96
and pest attacks	
3.3.4.4 The damages of the endpoints of	98
the planks	
3.3.5 The Hip Roof	98
3.3.5.1 Crack of the roof ridges	98
3.3.5.2 The aging of wood and the fungal	99
and pest attacks	2
3.3.5.3 Cracks of the timber truss frames	99
3.3.5.4 Destructions of <i>Liet</i> tiles	100
3.3.5.5 Man-made destructions 3.3.6 The Entrance Doors using filled-in Horizontal	101 103
3.3.6 The Entrance Doors using filled-in Horizontal Wooden Panels & The Slat Shutter Windows	103
3.3.6.1 The aging of wood and fungal and	103
pest attacks	103
3.4 Conclusions of Chapter 3	104
5.4 Conclusions of Chapter 5	104
Chapter 4: Results – The Creation of <i>Tu Giac</i> Housing	
Conservation Prototype related to the Deterioration/Destruction of	
6 Outstanding Tu Giac House Characteristics	
4.1 The Load Bearing Walls	106
4.1.1 Charter & Principles	106
4.1.2 Conservation Methods	107
4.2 Two-Storey Buildings	108
4.2.1 Charter & Principles	108
4.2.2 Conservation Methods	108
4.3 The high-pitch Timber Stair	108
4.3.1 Charter & Principles	108
4.3.2 Conservation Methods	109
4.4 The Timber Floor on the 2 nd level	109
4.4.1 Charter & Principles	109
4.4.2 Conservation Methods	110
4.5 The Hip Roof	110
4.5.1 Charter & Principles	110
4.5.2 Conservation Methods	111

4.6 The Entrance Doors by horizontal wooden bars & The Shutter Windows	111
4.6.1 Charter & Principles	111
4.6.2 Conservation Methods	111
4.7 The Tu Giac Housing Conservation Prototype (TGCP)	111
4.8 Conclusions of Chapter 4	158
Chapter 5: The <i>Tu Giac</i> Prototype Applications and Conclusions	
5.1 An Example of Applying <i>Tu Giac</i> Conservation Prototype on	159
Similar Buildings in Similar Climate: A Case Study of Wat-Ket	
houses, Chiang Mai, Thailand	
5.1.1 The historical background of the Wat-Ket area	159
5.1.2 The selected Historical Houses to promote <i>Tu</i>	161
Giac Conservation Prototype Applications	١.
5.1.2.1 The 2-Storey Historical House	162
5.1.2.2 The 1-Storey Historical House	166
5.1.3 The <i>Tu Giac</i> Conservation Prototype –	169
Application: TGCP-AP	100
5.2 Conclusions of Chapter 5	186
5.3 Conclusions	187
5.4 Recommendations	189
Bibliography	191
Appendices	194
Curriculum Vitae	203
	203
25	
AI UNIVERSIT	

ลิขสิทธิ์มหาวิทยาลัยเชียงใหม่ Copyright[©] by Chiang Mai University All rights reserved

List of Figures

Figu	re	Source	Page
1.1	World map shows the location of Vietnam in the South-East Asia.	Internet	2
1.2	The climate zone world map addresses Vietnam in the tropical zone.	Internet	3
1.3	The Vietnam contacting the sea becomes the place of transit for international trading sea routes.	Internet	4
1.4	The Dong Son bronze representing the Dong Son culture in the 3 rd millennium BC.	Internet	5
1.5	The distribution of Vietnamese and French architecture in three main cities of Vietnam.		9
1.6	Geographical situation of Hue city showing the relationship of Bao Vinh outwards (12km from the sea by river-transportation) and inwards close to the Citadel (1km) and Hue	T.B.Tinh, 2004	11
1.7	modern centre (5km). The location of Bao Vinh Village near the Huong River (the trading route to Hue from the sea-direction at that time) made it become the famous commercial river-port of Hue city	25	12
1.8	in the 19 th and early 20 th century. The Bao Vinh was founded after the demolishment of the previous Thanh Ha riverport.		15
1.9	Bao Vinh village site map shows the 9 Tu Giac houses, the outstanding French- influenced architecture of Hue city, on the riverside to develop trading here previously	Bao Vinh People Committee, 2007	17
1.10	Research Design.		23
2.1	The Citadel of Nguyen Dynasty (1802-1945)	·	29
2.2	with the outstanding royal buildings. Some examples of the conservation work on the Citadel.	ยเชยอ	30
2.3	The overall map of Hue city addressing the common distribution of Ruong house in Hue	T.B.Tinh, 2004	311
2.4	City in comparison with the location of Tu Giac houses only in the Bao Vinh Village. The Section and Façade of a typical 3-compartment <i>Ruong</i> house in Hue City	eserv	e 0
2.5	Some examples of the conservation work on Ruong houses - The conservation techniques for repairing decayed timber elements of <i>Ruong</i> houses.	Hue Heritage House Organization, 2003	33

2.6	The 9 <i>Tu Giac</i> houses on the riverside in Bao Vinh village. House No.5 had been	35
	demolished in September of 2007.	
2.7	The functional significance of <i>Tu Giac</i> House	36
2.1	for Bao Vinh is the storage space on the 2^{nd}	30
	level when the water tide is high.	
2.8	The development of the 2 nd floor of <i>Tu Giac</i> N.H.Quynh, 2002	37
2.0	houses from the wooden ceiling of <i>Ruong</i> & T.B.Tinh, 2004	31
	house and from Vietnamese traditional stilt-	
	houses to store and protect things from	
	moisture on the ground.	
2.9	The similarity of sloping roof in Hue	38
2.9	traditional architecture and <i>Tu Giac</i> houses.	36
2 10	The <i>Liet</i> tiles on <i>Ruong</i> houses (<i>left</i>) and on	39
2.10	Tu Giac houses (right).	39
2 1 1	The difference of Hue traditional timber	39
2.11	structure and French-influenced load bearing	39
	walls.	
2 12	The common one-storey Ruong house (<i>left</i>) in T.B.Tinh, 2002	40
2.12	Hue traditional architecture and the two-storey	
	Tu Giac houses as the French influence	
	(right).	/ /
2.13	The correlation of Conservation Charters,	51
7,10	Laws and Principles into parts of <i>Tu Giac</i>	
	House.	
3.1	The timeline indicates that the 1-storey	54
	buildings were the most common and mostly	
	built in the period 1802 – 1975 (944/1042	
	houses). The 2-buildings were present since	
	French coming (1885), but having the modest	
	number of 11. During colonial period, the	
	French built about 240 buildings generally for	
	French offices and schools within 2 or 3	
. 9	stories. 8 <i>Tu Giac</i> houses built in the period	,
	1920-1945 are the strong reflection of French-	
	influenced architecture in Hue city.	
3.2	The diagram showing the outline of	55
Dy	The diagram showing the outline of methodology from step A where 6 outstanding architectural characteristics of <i>Tu Giac</i> house	SILY
	architectural characteristics of <i>Tu Giac</i> house	/
	being determined before feeding into step B	e 0
- "	and D. the related Charters and Principles of	
	Conservation of step C is fed in to support	
	step B and D. Finally, the 'conservation technique protetype' of Tu Giga houses is	
	technique prototype' of <i>Tu Giac</i> houses is	
	carried out.	

3.3	The correlation of acronym characters B, C, and D related to the 6 outstanding characters	56
	A_1 through A_6 of Tu $Giac$ houses.	
3.4	The same river-street direction of all 8 <i>Tu</i>	58
	Giac houses (left) leads to the same direction	
	of three load bearing walls of all <i>Tu Giac</i>	
	houses into the north, south, and east side	
	(right).	
3.5	The difference between Tu Giac houses and	59
0.0	other French-influenced buildings.	
3.6	The graphical analysis of the way of working	60
3.0	of the load bearing walls which makes Tu	00
	Giac houses become special and dissimilar to	
	common load bearing walls in Hue city.	
3.7	The Vo brick unit with bigger sizes than	61
	currently common brick unit.	
3.8	The percentage 2% of the 2-storey houses in	62
	the total Hue traditional houses (<i>Tu Giac</i> and	02
	Ruong houses) showing their very rareness in	Ш
	Hue traditional houses.	Ш
3.9	The dimensional comparison between <i>Tu Giac</i>	63
	houses with normal construction standards of	
	the current street-facing multi-storey houses in	
	Vietnam.	
3.10	The similarity of high pitch timber stair N.H.Quynh, 2002	64
3.10	among <i>Tu Giac</i> houses and other multi-storey	0.
	buildings of Hue traditional architecture.	
3.11	The dimensional comparison of the stair with	65
	the Vietnamese standards.	
3.12	The comparison between the normal standard	66
	stairs in Vietnamese 2-storey houses and the	
	high pitch stairs of <i>Tu Giac</i> houses shows the	
	reduction 92% of area (A) if using high pitch	
	stair.	
3.13	The saving of more than 90% of the small	66
	ground-floor spaces by using the high pitch	
	timber stairs in <i>Tu Giac</i> houses.	
3.14	The comparison of physical properties of <i>Kien</i> D.C.Dien, 2002	68
1 7	Kien wood (No.1) with other 16 species of	
	wood commonly used in Hue traditional	0 0
	houses.	
3.15	The new architecture of the Pyramid of the	69
	hip roof.	
3.16	The first step of constructing the roof ridges	70
	on 4 diagonal timber trusses.	
3.17	The composition of the hip roof by <i>Liet</i> tiles.	71

intersection of two sloping roof-planes. 3.19 The direction of roofing <i>Liet</i> tiles in the hip roof. 3.20 The composition of 3 <i>Liet</i> tile layers distinguishable from the current 1 tile-layer. 3.21 The differences between <i>Liet</i> tiles and the currently roof-tiles. 3.22 The entrance door using filled-in horizontal wooden panels in some old towns of Central Vietnam. 3.23 The shutter windows with its response to hot and humid climate are used for the 2 nd floor spaces of the <i>Tu Giac</i> houses. 3.24 The conservation method-itemized model of <i>Tu Giac</i> House with its Architectural Elements representing 6 Outstanding Characteristics A ₁ - A ₆ . 3.25 The defining of 8 existing <i>Tu Giac</i> houses which contain or lack of Architectural Elements in comparison with the typical <i>Tu Giac</i> House. 3.26 The comparison of thermal expansion coefficients of materials. 3.27 The cracks on the walls caused by uneven thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2 nd floor (left side) and on the ground floor (right side).
roof. 3.20 The composition of 3 <i>Liet</i> tile layers distinguishable from the current 1 tile-layer. 3.21 The differences between <i>Liet</i> tiles and the currently roof-tiles. 3.22 The entrance door using filled-in horizontal wooden panels in some old towns of Central Vietnam. 3.23 The shutter windows with its response to hot and humid climate are used for the 2 nd floor spaces of the <i>Tu Giac</i> houses. 3.24 The conservation method-itemized model of <i>Tu Giac</i> House with its Architectural Elements representing 6 Outstanding Characteristics A ₁ - A ₆ . 3.25 The defining of 8 existing <i>Tu Giac</i> houses which contain or lack of Architectural Elements in comparison with the typical <i>Tu Giac</i> House. 3.26 The comparison of thermal expansion coefficients of materials. 3.27 The cracks on the walls caused by uneven thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2 nd floor (left side) and
3.20 The composition of 3 Liet tile layers distinguishable from the current 1 tile-layer. 3.21 The differences between Liet tiles and the currently roof-tiles. 3.22 The entrance door using filled-in horizontal wooden panels in some old towns of Central Vietnam. 3.23 The shutter windows with its response to hot and humid climate are used for the 2 nd floor spaces of the Tu Giac houses. 3.24 The conservation method-itemized model of Tu Giae House with its Architectural Elements representing 6 Outstanding Characteristics A ₁ - A ₆ . 3.25 The defining of 8 existing Tu Giac houses which contain or lack of Architectural Elements in comparison with the typical Tu Giac House. 3.26 The comparison of thermal expansion coefficients of materials. 3.27 The cracks on the walls caused by uneven thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2 nd floor (left side) and
distinguishable from the current 1 tile-layer. 3.21 The differences between <i>Liet</i> tiles and the currently roof-tiles. 3.22 The entrance door using filled-in horizontal wooden panels in some old towns of Central Vietnam. 3.23 The shutter windows with its response to hot and humid climate are used for the 2 nd floor spaces of the <i>Tu Giac</i> houses. 3.24 The conservation method-itemized model of <i>Tu Giac</i> House with its Architectural Elements representing 6 Outstanding Characteristics A ₁ - A ₆ . 3.25 The defining of 8 existing <i>Tu Giac</i> houses which contain or lack of Architectural Elements in comparison with the typical <i>Tu Giac</i> House. 3.26 The comparison of thermal expansion coefficients of materials. 3.27 The cracks on the walls caused by uneven thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2 nd floor (left side) and
currently roof-tiles. 3.22 The entrance door using filled-in horizontal wooden panels in some old towns of Central Vietnam. 3.23 The shutter windows with its response to hot and humid climate are used for the 2 nd floor spaces of the <i>Tu Giac</i> houses. 3.24 The conservation method-itemized model of <i>Tu Giac</i> House with its Architectural Elements representing 6 Outstanding Characteristics A ₁ - A ₆ . 3.25 The defining of 8 existing <i>Tu Giac</i> houses which contain or lack of Architectural Elements in comparison with the typical <i>Tu Giac</i> House. 3.26 The comparison of thermal expansion coefficients of materials. 3.27 The cracks on the walls caused by uneven thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2 nd floor (left side) and
3.22 The entrance door using filled-in horizontal wooden panels in some old towns of Central Vietnam. 3.23 The shutter windows with its response to hot and humid climate are used for the 2 nd floor spaces of the <i>Tu Giac</i> houses. 3.24 The conservation method-itemized model of <i>Tu Giac</i> House with its Architectural Elements representing 6 Outstanding Characteristics A ₁ - A ₆ . 3.25 The defining of 8 existing <i>Tu Giac</i> houses which contain or lack of Architectural Elements in comparison with the typical <i>Tu Giac</i> House. 3.26 The comparison of thermal expansion coefficients of materials. 3.27 The cracks on the walls caused by uneven thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2 nd floor (left side) and
wooden panels in some old towns of Central Vietnam. 3.23 The shutter windows with its response to hot and humid climate are used for the 2 nd floor spaces of the <i>Tu Giac</i> houses. 3.24 The conservation method-itemized model of <i>Tu Giac</i> House with its Architectural Elements representing 6 Outstanding Characteristics A ₁ - A ₆ . 3.25 The defining of 8 existing <i>Tu Giac</i> houses which contain or lack of Architectural Elements in comparison with the typical <i>Tu Giac</i> House. 3.26 The comparison of thermal expansion coefficients of materials. 3.27 The cracks on the walls caused by uneven thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2 nd floor (left side) and
Vietnam. 3.23 The shutter windows with its response to hot and humid climate are used for the 2 nd floor spaces of the <i>Tu Giac</i> houses. 3.24 The conservation method-itemized model of <i>Tu Giac</i> House with its Architectural Elements representing 6 Outstanding Characteristics A ₁ - A ₆ . 3.25 The defining of 8 existing <i>Tu Giac</i> houses which contain or lack of Architectural Elements in comparison with the typical <i>Tu Giac</i> House. 3.26 The comparison of thermal expansion coefficients of materials. 3.27 The cracks on the walls caused by uneven thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2 nd floor (left side) and
 3.23 The shutter windows with its response to hot and humid climate are used for the 2nd floor spaces of the <i>Tu Giac</i> houses. 3.24 The conservation method-itemized model of <i>Tu Giac</i> House with its Architectural Elements representing 6 Outstanding Characteristics A₁- A₆. 3.25 The defining of 8 existing <i>Tu Giac</i> houses which contain or lack of Architectural Elements in comparison with the typical <i>Tu Giac</i> House. 3.26 The comparison of thermal expansion coefficients of materials. 3.27 The cracks on the walls caused by uneven thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2nd floor (left side) and
and humid climate are used for the 2 nd floor spaces of the <i>Tu Giac</i> houses. 3.24 The conservation method-itemized model of <i>Tu Giac</i> House with its Architectural Elements representing 6 Outstanding Characteristics A ₁ - A ₆ . 3.25 The defining of 8 existing <i>Tu Giac</i> houses which contain or lack of Architectural Elements in comparison with the typical <i>Tu Giac</i> House. 3.26 The comparison of thermal expansion coefficients of materials. 3.27 The cracks on the walls caused by uneven thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2 nd floor (left side) and
spaces of the <i>Tu Giac</i> houses. 3.24 The conservation method-itemized model of <i>Tu Giac</i> House with its Architectural Elements representing 6 Outstanding Characteristics A ₁ - A ₆ . 3.25 The defining of 8 existing <i>Tu Giac</i> houses which contain or lack of Architectural Elements in comparison with the typical <i>Tu Giac</i> House. 3.26 The comparison of thermal expansion coefficients of materials. 3.27 The cracks on the walls caused by uneven thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 3 nd floor (left side) and
3.24 The conservation method-itemized model of <i>Tu Giac</i> House with its Architectural Elements representing 6 Outstanding Characteristics A ₁ - A ₆ . 3.25 The defining of 8 existing <i>Tu Giac</i> houses which contain or lack of Architectural Elements in comparison with the typical <i>Tu Giac</i> House. 3.26 The comparison of thermal expansion coefficients of materials. 3.27 The cracks on the walls caused by uneven thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 3 nd floor (left side) and
Tu Giac House with its Architectural Elements representing 6 Outstanding Characteristics A ₁ - A ₆ . 3.25 The defining of 8 existing Tu Giac houses which contain or lack of Architectural Elements in comparison with the typical Tu Giac House. 3.26 The comparison of thermal expansion coefficients of materials. 3.27 The cracks on the walls caused by uneven thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2 nd floor (left side) and
Elements representing 6 Outstanding Characteristics A ₁ - A ₆ . 3.25 The defining of 8 existing <i>Tu Giac</i> houses which contain or lack of Architectural Elements in comparison with the typical <i>Tu Giac</i> House. 3.26 The comparison of thermal expansion coefficients of materials. 3.27 The cracks on the walls caused by uneven thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2 nd floor (left side) and
Characteristics A ₁ - A ₆ . 3.25 The defining of 8 existing <i>Tu Giac</i> houses which contain or lack of Architectural Elements in comparison with the typical <i>Tu Giac</i> House. 3.26 The comparison of thermal expansion coefficients of materials. 3.27 The cracks on the walls caused by uneven thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 3 nd floor (left side) and
 3.25 The defining of 8 existing <i>Tu Giac</i> houses which contain or lack of Architectural Elements in comparison with the typical <i>Tu Giac</i> House. 3.26 The comparison of thermal expansion coefficients of materials. 3.27 The cracks on the walls caused by uneven thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2nd floor (left side) and
which contain or lack of Architectural Elements in comparison with the typical <i>Tu Giac</i> House. 3.26 The comparison of thermal expansion coefficients of materials. 3.27 The cracks on the walls caused by uneven thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2 nd floor (left side) and
Elements in comparison with the typical <i>Tu Giac</i> House. 3.26 The comparison of thermal expansion coefficients of materials. 3.27 The cracks on the walls caused by uneven thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2 nd floor (left side) and
Giac House. 3.26 The comparison of thermal expansion coefficients of materials. 3.27 The cracks on the walls caused by uneven thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2 nd floor (left side) and
 3.26 The comparison of thermal expansion coefficients of materials. 3.27 The cracks on the walls caused by uneven thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2nd floor (left side) and
coefficients of materials. 3.27 The cracks on the walls caused by uneven thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2 nd floor (left side) and
 3.27 The cracks on the walls caused by uneven thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2nd floor (left side) and
thermal movement between plaster and brick. 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2 nd floor (left side) and
 3.28 The uneven subsidence of two vertical sections (1 & 2) of a single back-wall causes the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2nd floor (left side) and
the vertical crack which tends to separate the wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2 nd floor (left side) and
wall into 2 vertical parts. 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2 nd floor (left side) and
 3.29 The subsidence of the whole foundation backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2nd floor (left side) and
backwards creates shear forces in walls. It results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2 nd floor (left side) and
results in the horizontal cracks which are liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2 nd floor (left side) and
liable to divide the wall into 2 horizontal parts. 3.30 Moss appears on the lower parts of the load 86 hearing walls on the 2 nd floor (left side) and
parts. 3.30 Moss appears on the lower parts of the load bearing walls on the 2 nd floor (left side) and
bearing walls on the 2 nd floor (left side) and
bearing walls on the 2 nd floor (left side) and
bearing wans on the 2 moof (left side) and
on the ground floor (right side).
3.31 Fungi and moulds have grown on the below 87
part of the walls on the ground floor (left side)
and on the 2 nd floor (right side).
3.32 The flooding in Bao Vinh (in 2008) and the
flakiness of the plaster and finishing on the
below parts of the load bearing walls caused
by flood.

3.33	The flakiness of isolated regions of plaster	88
	caused by the development of cracks (left) and	
	by the aging process of mortar (right) has	
2 2 4	made Vo bricks exposed to outside.	00
3.34	The flakiness of finishing layers, the calcium-	89
	originated whitewash, on the load bearing	
2.25	walls.	00
3.35	The holes created on the walls for hanging	89
	things or objects have been destroying the	
2.26	surfaces of the load bearing walls.	00
3.36	The additional parts on the 2 nd floor	90
	conflicting with the hip roofs have destroyed	
	the special scales in façades of the <i>Tu Giac</i>	
	original two-storey fabric, shown clearly in	
	the façade analysis (above) and the real photos	
	(below).	\I
3.37	The cracks on the wood surface of the stairs	91
1 5	caused by thermal movement.	
3.38	The aging process of wood and fungal attacks	92
	on their surfaces.	
- 1	The damaged endpoints of the stairs.	92
3.40	The moving to the other place outside the	93
	original structure of <i>Tu Giac</i> house and its	
	stair hole left with the new wooden planks (2	
	photos on left sides) – the changing into new	
	material of concrete of the timber stair (right	
	side).	
3.41	The encroachment of the stair-holes by	94
	disordered wooden planks has affected the	
	outstanding characteristic of the timber stair.	
3.42	Isostatics are contour lines of tension (dotted	94
	lines) and compression (solid lines). The	
	intersection of lines shows shear. The	
. 9	closeness of the contours expresses the	,
	intensity of stress. It indicates that tension is	
	greatest at the bottom and compression is	
	biggest on the top of the beam at mid-span.	
DY	Shear is greatest at the ends. It accounts for	'SIT'
	the appearance of cracks along the below half	/
	of the beam due to excessive tensions.	0
3.43	The structural cracks along the below half of	95
	the floor beams caused by their weakness in	
	withstanding the tension stresses.	
3.44	Cracks appeared on the wooden surfaces of	95
	the floor beam (left) and planks (right) caused	
	by thermal movement.	

	3.45	The poor-quality planks used as the substitutes for the original ones with the covering of	96	
		sticking-plasters on opening slits in between (left).		
	3.46	Fungal attacks with white flecks on the	97	
		wooden surfaces of the floor planks.		
	3.47	Floor beams and planks are attacked by termites.	97	
	3.48	Deterioration of the endpoints of the timber floor planks.	98	
	3.49	The cracks of the roof ridges on the top.	98	
		Fungal attacks (left and middle) and termite	99	
		attacks (right) on the elements of the timber		
		frame system of hip roof.		
	3.51	Cracks caused by thermal movement appear	100	
		on the horizontal (left) and vertical trusses	11	
		(right) of the timber frame system.		
		Mosses grow on the top surfaces of <i>Liet</i> tiles.	100	
	3.53	Mould and fungi on the surfaces of <i>Liet</i> tiles	101	
	M.,	due to high moisture content inside the house.		
	3.54	Iron plate is used to seal the holes on the roof	101	
	2.55	for water-proof.	100	
	3.55	The filling of mortar on the roof to prevent	102	
	2 56	water-penetration. Iron nails fixed on timber elements cause rots	102	
	3.30	of them.	102	
	3 57	Holes, cracks and rottenness are created on the	103	
	3.37	surfaces of wooden doors and windows by	103	
		pest and fungal attacks and the aging process		
		of wood.		
	4.1	A Table showing 15 conservation techniques	113	
		for Tu Giac houses (Drawing P-01 through P-		
		22).		
	4.2	The 15 conservation techniques in relation to	114	
		the 6 Architectural Characteristics (A ₁ through		
		A_6)		
	4.3	The method DP for the Prevention and	157	
	ΟУ	Maintenance. by Chiang Mai Univer	5	Į.
ì	5.1	The location of Wat-Ket addressing the	160	4
	<i>5</i> 2	historic houses for applications.	161	
-	5.2	The site map showing the location of two	161	1
	5 2	selected historic houses for applications. The selected 2 storay historic house in Wet	162	
	5.3	The selected 2-storey historic house in Wat Ket: VILLA CINI for applications.	102	
	5.4	The <i>Tu Giac</i> Conservation Methods	163	
	J. T	applicable for the VILLA CINI house in Wat-	103	
		Ket area, Chiang Mai, Thailand.		

5.5	The selected 1-storey historic house in Wat-	166
	Ket: The Gallery for applications.	
5.6	The interior of the selected 1-storey historic	167
	house.	
5.7	The <i>Tu Giac</i> Conservation Methods	167
	applicable for the The Gallery house in Wat-	
	Ket area, Chiang Mai, Thailand.	
5.8	11 techniques out of 15 <i>Tu Giac</i> conservation	172
	techniques are applicable for Wat Ket –	
	VILLA CINI in Chiang Mai, Thailand.	
5.9	9 techniques out of 15 <i>Tu Giac</i> conservation	180
	techniques are applicable for Wat Ket – The	
	Gallery in Chiang Mai, Thailand.	
		\ \
		11
		5
11		
	\bigcirc	//
	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	
	YAT TINITITES	
	UNIVE	

ลิขสิทธิ์มหาวิทยาลัยเชียงใหม่ Copyright[©] by Chiang Mai University All rights reserved

Abbreviations and Symbols

Tu Giac: Vietnamese name of the Pyramid.

Original: preceding all others in time or being as first made or performed.

Conservation, Preservation: means all the processes of preventing the loss or

damage or other change of original elements.

Authenticity: undisputed credibility.

Prototype: a standard or typical example.

